

GLASS DOOR REFRIGERATOR

- * CFC Free
- * Exterior sign light
- * White aluminium construction
- * Interior light
- * Bottom mounted compressor
- * Manual temperature control
- * Easy maintenance
- * Double pane tempered glass
- * Evaporator pan
- * **NA-24**
Swing and self-closing door
4 adjustable epoxy shelves
- * **NA-40 | NA-55**
gravity self-closing doors
Digital thermometer
8 adjustable epoxy shelves
Option: Casters



NA-40R



NA-24R



NA-55R

Warranty:

1 year parts and labor
5 years on compressor only



GLASS DOOR REFRIGERATOR



Model	NA-24-R	NA-40-R	NA-55-R
Capacity	300 l 14 pi³/cu.ft.	800 l 22 pi³/cu.ft.	1200 l 30 pi³/cu.ft.
Temperature	0-10°C	0-10°C	0-10°C
Refrigerant	R134A	R134A	R134A
Outside Dimensions	24" x 24" x 73.5" 609.6 x 609.6 x 1866.9 (mm)	40" x 25.75" x 79.5" 1016 x 654 x 2019 (mm)	53.5" x 25.75" x 79.5" 1359 x 654 x 2019 (mm)
Interior Dimensions	19.7" x 20" x 48.4" 500 x 510 x 1230 (mm)	35.25" x 20" x 53" 895 x 508 x 1346 (mm)	49" x 20" x 53" 1245 x 508 x 1346 (mm)
Shipping Dimensions	26.9" x 28.5" x 76" 683 x 724 x 1930 (mm)	29.75" x 42.63" x 77.5" 756 x 1083 x 1969 (mm)	30.75" x 56.5" x 77.5" 781 x 1435 x 1969 (mm)
Compressor	1/4 H.P.	3/8 H.P. Danfoss	1/2 H.P. Danfoss
Voltage	110V / 60HZ	110V / 60HZ	110V / 60HZ
Ampere	4.8A	7.9A	8.6A
Length of cable	2.3m 7.55 pi/ft	2.3m 7.55 pi/ft	2.3m 7.55 pi/ft
Net weight	209.4 lb(s) 95 kg	237 lb(s) 153 kg	430 lb(s) 195 kg
Shelves dimensions	19" x 18.5" 483.5 x 470 (mm)	19" x 16.75" 483.5 x 426 (mm)	19" x 23.75" 483.5 x 603 (mm)
Insulation thickness	2.3" 60mm	2.3" 60mm	2.3" 60mm

August 09

Design and specifications can change without prior notice for product improvement.



DISTRIBUTED BY:



129 Montée de Liesse
St-Laurent (QC) H4T 1T9
Tel: (800) 567-3620
Fax: (514) 382-7837

6355 Danville Road, Unit 8
Mississauga (ON) L5T 2L4
Tel: (888) 645-7324
Fax: (905) 565-5992

9912 Lougheed Highway
Burnaby (BC) V3J 1N3
Tel: (888) 655-3620
Fax: (604) 444-3697

THE SOLUTION IN RESTAURANT EQUIPMENT